

Day & Night IR Dome Camera

**SPECTRUM
SELECT**

Rugged dome



Features

- 1/3" SONY COLOR CCD
- 480 TVL / 0.5 Lux Min. illumination
- Color in daytime, B/W by night
- Super Bright 21 pcs IR LED
- Ceiling and wall mount
- Entire Aluminum Alloy with Anode
- High Sensitivity
- Excellent Image Quality
- Cost-Performance
- Vandal Proof

Specifications

Model	NTSC	Q8N31171-301	Q8N32371-301
	PAL	Q8P31171-301	Q8P32371-301
Image device	1/3" SONY COLOR CCD		1/3" SHARP COLOR CCD
Min. illumination	0.5 lx at F1.4 / 0 Lux (IR ON)		
Synchronization	Internal synchronous		
Resolution	480 TVL		380 TVL
Picture elements	NTSC	380K Pixel	250K Pixel
	PAL	440K Pixel	290K Pixel
Lens	Fixed lens 6mm or 8mm		
S/N Ratio	50dB (AGC OFF)		
Electronic shutter	NTSC:1/60 ~ 1/100,000 Sec. / PAL:1/50 ~ 1/100,000 Sec.		
Video output	1.0 Vp-p Composite, 75Ω		
Gamma correction	0.45		
Auto gain control	AUTO / OFF		
White balance	AUTO / TRACING		
BLC	ON / OFF		
Flicker less	Fixed shutter @ 1/50		
Mirror Function	On/Off		
Power supply	DC8V~18V / 120mA (Max)		
Ambient Operation	-10°C ~ 50°C / 30% ~ 90% RH		
Installation location	Indoor		
Weight	Apprx. 450g		
Dimensions	68(W) x 74(H) mm		
IR LED	21 pcs (850nm)		

© Specifications subject to change without notice V1.1